



Perfect sparkle, mini design

MASTERColour CDM-Tm Elite Mini

Mini, single-ended, very high-efficiency, long-life Ceramic Metal Halide discharge lamp producing crisp white sparkling light with high color rendering

Benefits

- High-intensity beam of crisp white sparkling light makes merchandise look irresistible
- Lowest Total Cost of Ownership as a result of high efficacy (same light, less energy or same energy, more light) and long life
- Fits in small luminaires which are less visible

Features

- Crisp white sparkling light
- Excellent color rendering, with extra red
- High efficacy with unparalleled lumen maintenance
- Stable color performance over lifetime
- Mini size

Application

- Accent and display lighting in retail
- General and decorative indoor lighting
- Outdoor area lighting

MASTERColour CDM-Tm Elite Mini

Warnings and Safety

- Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures
- Use only with electronic control gear
- For 50W use with Philips electronic gear only
- Control gear must include end-of-life protection (IEC61167, IEC 62035)
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Versions



MASTERColour CDM-Tm /830, /
930, /942 GU6.5

Dimensional drawing

D

Product	D (max)	D	O	L (min)	L (max)	L	C (max)
MASTERColour CDM-Tm Elite Mini 35W/930 GU6.5 1CT	13.3 mm	0.5 in	4.7 mm	28 mm	32 mm	30 mm	56.7 mm
MASTERColour CDM-Tm Elite Mini 20W/830 GU6.5 1CT	13.3 mm	0.5 in	3.4 mm	28 mm	32 mm	30 mm	56.7 mm

MASTERCcolour CDM-Tm Elite Mini

Controls and dimming

Dimmable	No
----------	----

Operating and electrical

Re-ignition Time (Min) (Max)	15 min
------------------------------	--------

General information

Cap-Base	GU6.5
Life To 10% Failures (Nom)	14000 h
Life To 20% Failures (Nom)	16000 h
Life To 50% Failures (Nom)	20000 h
Life To 5% Failures (Nom)	12000 h
Operating Position	UNIVERSAL

Light technical

Chromaticity Coordinate X (Nom)	0.434
Chromaticity Coordinate Y (Nom)	0.398
Color Designation	Warm White (WW)
Correlated Color Temperature (Nom)	3000 K

Mechanical and housing

Bulb Finish	Clear
-------------	-------

Approval and application

Order Code	Full Product Name	Energy Consumption	Mercury (Hg)	Mercury (Hg)
		kWh/1000 h	Content (Max)	Content (Nom)
928183505130	MASTERCcolour CDM-Tm Elite Mini 20W/830 GU6.5 1CT	21 kWh	3.5 mg	3.5 mg
928187405130	MASTERCcolour CDM-Tm Elite Mini 35W/930 GU6.5 1CT	40 kWh	4.7 mg	4.7 mg

Operating and electrical

Order Code	Full Product Name	Voltage (Max)	Voltage (Min)	Voltage (Nom)	Power (Nom)
928183505130	MASTERCcolour CDM-Tm Elite Mini 20W/830 GU6.5 1CT	100 V	90 V	95 V	20.1 W

Order Code	Full Product Name	Voltage (Max)	Voltage (Min)	Voltage (Nom)	Power (Nom)
928187405130	MASTERCcolour CDM-Tm Elite Mini 35W/930 GU6.5 1CT	95 V	79 V	87 V	39.1 W

Luminaire design requirements

Order Code	Full Product Name	Bulb Temperature (Max)
928183505130	MASTERCcolour CDM-Tm Elite Mini 20W/830 GU6.5 1CT	380 °C

Order Code	Full Product Name	Bulb Temperature (Max)
928187405130	MASTERCcolour CDM-Tm Elite Mini 35W/930 GU6.5 1CT	450 °C

Light technical (1/2)

Order Code	Full Product Name	Color			Lumen Maintenance
		Color Code	Color Rendering Index (Min)	Color Rendering Index (Nom)	
928183505130	MASTERCcolour CDM-Tm Elite Mini 20W/830 GU6.5 1CT	830	81	84	91 %

Order Code	Full Product Name	Color			Lumen Maintenance
		Color Code	Color Rendering Index (Min)	Color Rendering Index (Nom)	
928187405130	MASTERCcolour CDM-Tm Elite Mini 35W/930 GU6.5 1CT	930	87	90	95 %

Light technical (2/2)



MASTERColour CDM-Tm Elite Mini

Order Code	Full Product Name	Lumen	Lumen	Lumen	Lumen	Lumen	Luminous	Luminous	Luminous	Luminous
		Maintenance	Maintenance	Maintenance	Maintenance	Maintenance	Efficacy			
		10000 h (Nom)	12000 h (Nom)	2000 h (Nom)	4000 h (Nom)	5000 h (Nom)	(rated)	Flux (Nom)	(Min)	(Nom)
928183505130	MASTERColour CDM-Tm Elite Mini 20W/830 GU6.5 1CT	78 %	77 %	87 %	84 %	83 %	90 lm/W	1800 lm	1620 lm	1800 lm
928187405130	MASTERColour CDM-Tm Elite Mini 35W/930 GU6.5 1CT	-	80 %	93 %	90 %	-	102 lm/W	4000 lm	3600 lm	4000 lm

Mechanical and housing

Order Code	Full Product Name	Bulb Shape	Order Code	Full Product Name	Bulb Shape
928183505130	MASTERColour CDM-Tm Elite Mini 20W/830 GU6.5 1CT	T-4	928187405130	MASTERColour CDM-Tm Elite Mini 35W/930 GU6.5 1CT	T13.3

Colour Rendering Diagrams



LDCR_CDM-Tm_35W_930_GU65-Colour rendering diagram

MASTERColour CDM-Tm Elite Mini

