



The new Coreline slim batten is slim design and come in 3 sizes and 2 CCT choices based on specific customer needs.

Coreline Slim Batten

The new Philips Coreline slim batten offers exceptional value. It is Perfect for your everyday lighting installations. Available in 3 standard sizes, and 2 CCTs to provide flexibility to customer.

Benefits

- Slim and Robust design
- 50K Hours Life L70B50
- 5 Years warranty

Features

- Energy efficient with long service life. (50 000 hours - L70)
- 5 Years Warranty
- IP20, IK04
- CRI80
- 3 Different sizes L600/L1200/L1500 and 2 Different CCT (4000K/6500K) choices

Coreline Slim Batten

Application

- Offices
- Residential
- Parking Garages

Versions



Application Conditions

Ambient temperature range -20 to +40 °C

Approval and Application

Mech. impact protection code IK04

Ingress protection code IP20(front IP40)

Controls and Dimming

Dimmable No

Operating and Electrical

Input Voltage 220 to 240 V

General Information

CE mark CE mark

Protection class IEC Safety class I

Optical cover/lens type Polycarbonate
Diffuser

Initial Performance (IEC Compliant)

Init. Corr. Color Temperature 4000 K

Init. Color Rendering Index >80

Luminous flux tolerance +/-10%

Mechanical and Housing

Color White RAL 9003

Initial Performance (IEC Compliant)

Order Code	Full Product Name	Initial LED luminaire efficacy	Initial luminous flux	Initial input power
911401898780	BN126C LED22S/840 PSU L600	104 lm/W	2200 lm	21 W
911401898980	BN126C LED41S/840 PSU L1200	107 lm/W	4100 lm	38 W
911401899180	BN126C LED60S/840 PSU L1500	107 lm/W	6000 lm	56 W

Coreline Slim Batten

