



UniStrip G4

BCP382 36LED 30K 24V 40 L100

3000 K

UniStrip G4 is a surface mounted, exterior-rated LED luminaire that is designed for façade and outdoor architectural lighting applications. One family that fits all your needs, wall washing, grazing and also linear flood lighting. The robust mechanical and unique optical designs make it ideal for illuminating buildings facades, bridges, overpasses and any application that requires a linear lighting solution. Available in white, monochromatic colors, RGB, RGBW and tunable white and DMX control option available with up to 8 pixels (8IDs) to give architects and designers the freedom to explore a wide range of concepts and design with no limitations.

Warnings and Safety

- For outdoor use only

Product data

General Information		Luminaire light beam spread	
Light source replaceable	No	40° x 40°	
Driver included	No	Operating and Electrical	
Light source engine type	LED	Input Voltage	24 DC V
Lighting Technology	LED	Line Frequency	- Hz
Light Technical		Input Frequency	- Hz
Luminous Flux	2,367 lumen	Power Factor (Fraction)	0.9
Correlated Color Temperature (Nom)	3000 K	Connection	2 Push-in connector 2-pole
Luminous Efficacy (rated) (Nom)	66 lm/W	Cable	2 cables 0.15m with connectors 2-pole
Color rendering index (CRI)	80	Temperature	
Light source color	Warm white	Ambient temperature range	-40 to +50 °C
Optical cover/lens type	Clear flat		

UniStrip G4

Controls and Dimming

Dimmable	No
Control interface	-

Mechanical and Housing

Housing Material	Aluminum extruded
Optic material	Polymethyl methacrylate
Optical cover/lens material	Tempered glass
Fixation material	Aluminum
Housing Color	Dark gray
Mounting device	Mounting bracket adjustable
Optical cover/lens finish	Clear
Overall length	1,000 mm
Overall width	38 mm
Overall height	47 mm
Dimensions (Height x Width x Depth)	47 x 38 x 1000 mm

Approval and Application

Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [1 J]

Protection class IEC	Safety class III
Flammability mark	For mounting on normally flammable surfaces
CE mark	CE mark

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	4 SDCM
Power consumption tolerance	+/-10%

Product Data

Full product code	911401739442
Order product name	BCP382 36LED 30K 24V 40 L100
Order code	911401739442
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material number (12NC)	911401739442
Full product name	BCP382 36LED 30K 24V 40 L100



Dimensional drawing

