



HID-Basic Semi-Parallel ballasts for SON/CDM/MH lamps

BSN 250L 427I TS

The HID Basic Semi-Parallel ballast is an impregnated (HID standard) electromagnetic copper/iron ballast for use with an external ignitor for HID lamps.

Product data

General Information		Temperature	
Application Code	L427 ITS	T-Winding (Max)	130 °C
		Delta-T Normal Conditions	70 °C
Operating and Electrical		Approval and Application	
Input Voltage	230 V (default) or 240 V	Approval Marks	CE marking
Input Frequency	50 Hz		
Power Factor 100% Load (Min)	0.85	Product Data	
Mains Voltage Performance (AC)	-8%~+6%	Full product code	871016306808430
Mains Voltage Safety (AC)	-10%~+10%	Order product name	BSN 250L 427I TS
Input Current with PF Correction	1.4 A	EAN/UPC - Product	8710163150482
Input Current without PF Correction	3 A	Order code	913710100859
Power Factor without PF Compensation (Nom)	0.40	Numerator - Quantity Per Pack	1
Power Losses (Nom)	22.9/23.9 W	Numerator - Packs per outer box	6
		Material Nr. (12NC)	913710100859
Wiring		Net Weight (Piece)	2.950 kg
Connector Type	Screw		
System characteristics			
Rated Ballast-Lamp Power	250 W		

HID-Basic Semi-Parallel ballasts for SON/CDM/MH lamps

Dimensional drawing



Product	D1	C1	A1	A2	B1
BSN 250L 427I TS	6.2 mm	64.5 mm	150.0 mm	135 mm	75.5 mm

BSN 250 L427 ITS

