



# MASTER VALUE LEDspot MV

## Master LED 4.9-50W GU10 927 36D Dim

Delivering a warm, halogen-like accent beam, MASTER VALUE is a perfect fit for spot lighting. Thanks to its high CRI, it realizes more natural colors, creating cozy and comfortable ambiances for residential and hospitality projects, and emphasizing the beauty of merchandise in retail. These LED spots MV GU10 have the familiar look and feel of spot lamps, keeping the classic beauty of glass spots and adding the strong performance of LED technology. The dimming function enables you to create the atmosphere you desire, and it works with broad selection of dimmers. MASTER VALUE also offers more energy savings than normal LED spots.

### Warnings and Safety

- Operating temperature range is between -20° C and 45° C ambient
- Only to apply in dry or damp locations and most of open fixtures with lamp-holders that offer sufficient space (10 mm free air space)
- Not intended for use with emergency light fixtures or exit lights

### Product data

General Information	
Cap-Base	GU10 [GU10]
Nominal lifetime	25,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
Light Technical	
Color Code	927
Beam Angle (Nom)	36 degree(s)
Luminous Flux	395 lumen
Luminous Intensity (Nom)	650 cd

Color Designation	Warm White (WW)
Correlated Color Temperature (Nom)	2700 K
Luminous Efficacy (rated) (Nom)	80.61 lm/W
Color Consistency	<6
Color rendering index (CRI)	90
LLMF At End Of Nominal Lifetime (Nom)	70 %
Luminous Flux in 90° Cone (Rated)	355 lumen
Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz

# MASTER VALUE LEDspot MV

Lamp Current (Nom)	27 mA
Wattage Equivalent	50 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.8
Voltage (Nom)	220-240 V

## Temperature

T-Case Maximum (Nom)	80 °C
----------------------	-------

## Controls and Dimming

Dimmable	Yes
----------	-----

## Mechanical and Housing

Bulb Shape	PAR16 [PAR 2 inch/50mm]
------------	-------------------------


## Approval and Application

Suitable For Accent Lighting	Yes
Energy Consumption kWh/1000 h	5 kWh
EU RoHS compliant	Yes

## Product Data



Full product code	871869670731900
Order product name	Master LED 4.9-50W GU10 927 36D Dim
Order code	929001348808
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material number (12NC)	929001348808
Full product name	Master LED 4.9-50W GU10 927 36D Dim
EAN/UPC - Case	8718696707326

## Dimensional drawing



Product	D	C
Master LED 4.9-50W GU10 927 36D Dim	50 mm	54 mm


## Photometric data



Spectral Power Distribution Colour - Master LED 4.9-50W GU10 927 36D Dim


# MASTER VALUE LEDspot MV

## Photometric data



Light Distribution Diagram - Master LED 4.9-50W GU10 927 36D Dim

## Lifetime



Life Expectancy Diagram - Master LED 4.9-50W GU10 927 36D Dim

Lumen Maintenance Diagram - Master LED 4.9-50W GU10 927 36D Dim

