



**Philips BN058 offers exceptional value. It is Perfect for your everyday lighting installations. It provides quality light and substantial energy and maintenance savings.**

### **Essential Smartbright T5 Batten**

BN058 Batten provide flexibility to customer to choose from 3 CCT and 4 different size and lumen packages, based on their specific need.

#### **Benefits**

- Slim and trunkable, integrated design
- Polycarbonate housing with one pc extrusion process
- Slim profile: Ideal for task lighting / cove lighting applications

## Essential Smartbright T5 Batten

### Features

- 15,000 hrs life, L70/B50
- 1 Year warranty
- 4 lengths, 3 colors Increased number of options for easy application
- CRI 70, SDCM < 7, 85lm/W
- Mounting accessories included

### Application

- Hospitality
- Offices
- Residential

### Versions



Essential Smartbright T5 Batten, GCGM

Essential Smartbright T5 Batten, GCGM

Essential Smartbright T5 Batten, GCGM

Essential Smartbright T5 Batten, GCGM

# Essential Smartbright T5 Batten

## Application Conditions

Ambient temperature range -20 to +40 °C

## Approval and Application

Mech. impact protection code IK02

Ingress protection code IP20

## Controls and Dimming

Dimmable No

## Operating and Electrical

Input Voltage 220 to 240 V

## General Information

CE mark -

Protection class IEC Safety class II

Optical cover/lens type Polycarbonate

## Initial Performance (IEC Compliant)

Init. Color Rendering Index >70

Initial LED luminaire efficacy 85 lm/W

Luminous flux tolerance +/-10%

## Mechanical and Housing

Color White

## Initial Performance (IEC Compliant)

Order Code	Full Product Name	Init. Corr. Color Temperature	Initial luminous flux	Initial input power
911401709522	BN058C LED11/WW L1200 GM	3000 K	1200 lm	13 W
911401709532	BN058C LED11/NW L1200 GM	4000 K	1200 lm	13 W
911401709542	BN058C LED11/CW L1200 GM	6500 K	1200 lm	13 W
911401709552	BN058C LED9/WW L900 GM	3000 K	900 lm	9.6 W
911401709562	BN058C LED9/NW L900 GM	4000 K	900 lm	9.6 W
911401709572	BN058C LED9/CW L900 GM	6500 K	900 lm	9.6 W
911401709582	BN058C LED5/WW L600 GM	3000 K	600 lm	6.5 W
911401709592	BN058C LED5/NW L600 GM	4000 K	600 lm	6.5 W
911401709602	BN058C LED5/CW L600 GM	6500 K	600 lm	6.5 W
911401709612	BN058C LED3/WW L300 GM	3000 K	300 lm	3.4 W
911401709622	BN058C LED3/NW L300 GM	4000 K	300 lm	3.4 W
911401709632	BN058C LED3/CW L300 GM	6500 K	300 lm	3.4 W

